

SEMICONDUCTOR PACKAGE FOR ENHANCING HEAT
DISSIPATION

BACKGROUND OF THE INVENTION

1. Field of the invention

5 The present invention relates to a heat-dissipation-enhanced semiconductor package, and particularly to a heat-dissipation-enhanced semiconductor package which could be applied in a thin product for reducing the probability of product's delamination and the steps of manufacturing process.

10 **2. Description of the related art**

For the technology of semiconductor package, how to efficiently resolve the problem of heat dissipation is a very important issue. A semiconductor package with bad heat dissipation could not only create a series of errors, but also reduce the product reliability and increase much
15 manufacturing cost.

FIG. 1 shows a prior art DHS (Drop-in Heat Sink) structure of a semiconductor package disclosed in U.S. Patent No. 5,225,710. The package structure comprises: a die pad 14; a die 12, which is mounted to a first surface 141 of the die pad 14 with a die attach adhesive 15, such as a silver paste; a plurality of leads 13, which are electrically connected to an active surface 121 of the die 12 with a plurality of bonding wires 17, such as gold wires; the die pad 14 and the plurality of leads 13 are all a part of a leadframe; a heat sink 16, which is located inside the lower mold 19 and contacts the bottom of the lower mold 19 with contacts 161 and 162, and
20 another surface of the heat sink is attached to the second surface 142 of the die pad 14; and an encapsulant 11, which is injected to fill the molding cavity of the package structure when the upper mold 18 and lower mold 19 are closed. The characteristic of the prior art package structure is that the
25

heat generated by the die 12 could be dissipated from the die pad 14, through the heat sink 16 attached to the die pad 14 and then to the atmosphere.

FIG. 2 is a prior art EDHS (Exposed Drop-in Heat Sink) structure of a semiconductor package disclosed in U.S. Patent No. 5,381,042. The difference of the EDHS structure from the DHS structure is that a heat sink 21 with a flat bottom in the EDHS structure is directly exposed to the bottom of the semiconductor package unlike the heat sink 16 of the DHS structure contacting the bottom of the semiconductor package through the contacts 161 and 162. The exposed drop-in heat sink 21 has a larger contact area than the drop-in heat sink 16 to dissipate the heat. Therefore, the effect of heat dissipation in the EDHS structure is better than that in the DHS structure.

But both the DHS and EDHS structure have the following disadvantages:

1. During manufacturing processes, the heat sink should be put inside the lower mold 19 first, and the die pad 14 is then aligned to the heat sink. In other words, an extra process step is added, the cycle time of the manufacturing process is increased, and thus the throughput is reduced.
2. The drop-in heat sink 16 or the exposed drop-in heat sink 21 is covered by the encapsulant 11, but both the heat sinks and the encapsulant have different CTE (Coefficient of Thermal Expansion). When the structure suffers from expansion and shrinking, the effect of thermal stress will be created on the contact surface between the heat sink and the encapsulant, and delamination will be created on the contact surface. Besides, the amounts of the encapsulant 11 inside the upper mold 18 and lower mold 19 are not the same, and the package structure will be warped due to different shrinking strengths after being cooled. The moisture in the atmosphere will permeate into cracks caused by delamination or warping, and the reliability of the semiconductor package will be reduced.

3. Besides, when the encapsulate 11 is injected, the heat sink 21 is fixed by four tie bars on the diagonals of the leadframe (not shown). As the strength of the four tie bars are not necessarily large enough to fix the heat sink 21, some flashed encapsulant will be left on the bottom of the semiconductor package after encapsulation. The manufacturing cost will be increased because a deflashing action should be taken.

4. In the above two prior arts, the heat dissipation paths start from the die 12, through the die pad 14, then through the heat sinks 16 or 21, and to the atmosphere at last. Because the heat dissipation paths are limited; for example, the plurality of leads cannot be used for dissipating the heat, the efficiency of the heat dissipation will be reduced.

5. For some thin products, such as some consumer IC whose thickness P is less than 1.00mm (in other words, the thickness of the lower mold is less than 0.45mm), the heat sink 16 or 21 cannot be put inside the package due to small thickness.

SUMMARY OF THE INVENTION

The first object of the present invention is to propose a semiconductor package which has no need to put a heat sink inside the lower mold before it is encapsulated.

The second object of the present invention is to propose a semiconductor package which will not cause delamination due to different CTE between the encapsulant and the heat sink.

The third object of the present invention is to propose a semiconductor package which has no need to process a deflashing process.

The fourth object of the present invention is to propose a semiconductor package which could use a plurality of leads for dissipating the heat generated by the die.

The fifth object of the present invention is to propose a semiconductor package which could be applied in a thin product, such as TQFP (Thin Quad Flat Package) or TSOP (Thin Small Outline Package).

For achieving the above purposes, the present invention discloses a semiconductor package for enhancing heat dissipation. Only the upper mold is encapsulated, and a heat sink having a thickness variable with demands is mounted to the die pad and a part of the plurality of leads with a thermally conductive and electrically insulating adhesive glue. As the thickness of the heat sink is adjustable according to user's demands, and is not limited by the thickness specification of the lower mold in prior art, the present invention is more suitable for manufacturing thin products. The width of the heat sink covers the die pad and a part of the plurality of leads, therefore the heat generated by the die could be not only dissipated to the atmosphere through the heat sink and leadframe, but also dissipated through the heat sink and the printed circuit board mounted to the leads of the leadframe by conduction. In manufacturing process of the semiconductor package for enhancing heat dissipation, there is no need to be aligned accurately between the die pad and the heat sink, and is also no need to pressure the heat sink by the tie bars of the leadframe, therefore the cycle time of manufacturing process would be reduced, and the throughput would be raised. Besides, the heat sink according to the present invention is not encapsulated inside the lower mold, but mounted to the die pad and a part of the plurality of leads with an adhesive glue, therefore even the CTEs of the heat sink and encapsulant or the leadframe are not the same, the encapsulant will not be cracked or delaminated when the structure suffers from expansion and shrinking, and the reliability of the semiconductor package will be raised. Finally, even the flash is created when encapsulating the upper mold, and the bad appearance will be hidden after mounting the heat sink to the die pad and a part of the plurality of leads. In other words, the present invention would avoid the deflashing step in prior art.

The first embodiment of the semiconductor package for enhancing heat dissipation according to the present invention mainly comprises a die, a leadframe, an encapsulant and a heat sink. The leadframe includes a die pad having a first surface which the die is mounted to and a plurality of leads electrically connected to an active surface of said die through a plurality of bonding wires. The encapsulant is used to seal said die and leadframe. The heat sink is mounted to the second surface of the die pad and the plurality of leads with a thermally conductive and electrically insulating adhesive glue.

The second embodiment of the semiconductor package for enhancing heat dissipation according to the present invention mainly comprises a die, a leadframe, an encapsulant and a heat sink. The die includes an active surface and a second surface. The leadframe includes a central-hole die pad and a plurality of leads, wherein the central-hole die pad has a first surface which the die is mounted to and a second surface. The plurality of leads are electrically connected to the active surface of the die through a plurality of bonding wires. The encapsulant is used to seal the die and leadframe. The heat sink is a T-type structure, mounted to the second surface of the die, the second surface of the die pad and the plurality of leads with a thermally conductive and electrically insulating adhesive glue.

The third embodiment of the semiconductor package for enhancing heat dissipation according to the present invention mainly comprises a die, a leadframe, an encapsulant and a heat sink. The die includes an active surface. The leadframe includes a plurality of leads for mounting the die and a plurality of leads electrically connected to an active surface of the die through a plurality of bonding wires. The encapsulant is used to seal the die and leadframe. The heat sink is mounted to the plurality of leads with a thermally conductive and electrically insulating adhesive glue.

The manufacturing method of the first embodiment of the semiconductor package for enhancing heat dissipation according to the

present invention mainly comprises steps (a) to (d). In step (a), the die is mounted to the first surface of the die pad, and the plurality of bonding wires are used to electrically connect the active surface of the die and the plurality of leads. In step (b), an upper mold for sealing the die and leadframe is encapsulated. In step (c), the heat sink is mounted to the second surface of the die pad and a part of the plurality of leads with the thermally conductive and electrically insulating adhesive glue. In step (d), the leadframe is formed and singulated.

The manufacturing method of the second embodiment of the semiconductor package for enhancing heat dissipation according to the present invention mainly comprises steps (a) to (d). In step (a), the die is mounted to the first surface of the die pad, and the plurality of bonding wires are used to electrically connect the active surface of the die and the plurality of leads. In step (b), an upper mold for sealing the die and leadframe is encapsulated. In step (c), the heat sink is mounted to the second surface of the die, the second surface of the die pad and a part of the plurality of leads with the thermally conductive and electrically insulating adhesive glue. In step (d), the leadframe is formed and singulated.

The manufacturing method of the third embodiment of the semiconductor package for enhancing heat dissipation according to the present invention mainly comprises steps (a) to (d). In step (a), a die is mounted to the plurality of leads, and the plurality of bonding wires are used to electrically connect the active surface of the die and the plurality of leads. In step (b), only the upper mold for sealing said die and leadframe is encapsulated. In step (c), the heat sink is mounted to a part of the plurality of leads with the thermally conductive and electrically insulating adhesive glue. In step (d), the leadframe is formed and singulated.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will be described according to the appended drawings in which:

FIG. 1 is a prior art DHS structure of a semiconductor package;

FIG. 2 is a prior art EDHS structure of a semiconductor package;

FIGs. 3(a) to 3(d) show semi-products manufactured by a manufacturing process of the present invention;

5 FIG. 4 shows an embodiment of a cavity-down package structure according to the present invention;

FIG. 5 shows an embodiment of a package structure according to the present invention; and

10 FIG. 6 shows another embodiment of a package structure according to the present invention.

PREFERRED EMBODIMENT OF THE PRESENT INVENTION

15 FIGs. 3(a) to 3(d) show semi-products manufactured by the manufacturing process of the present invention. As shown in FIG. 3(a), a die 12 is mounted to a first surface 141 of the die pad 14 first, and the wiring bonding is processed between the active surface 121 of the die 12 and a plurality of leads 13. Afterwards, only the upper mold 18 is encapsulated.

20 As shown in FIG. 3(b), after the encapsulation of the upper mold 18, a heat sink 31 is mounted to the second surface 142 of the die pad 14 and a part of the plurality of leads 13 with adhesive glue 32. The thickness of the heat sink 31 could be suitably chosen according to the specification of the thin product. Therefore the limitation in prior art that the thickness of the heat sink should be less than that of the lower mold can be avoided in the present invention. The adhesive glue 32 should be a thermally conductive
25 but not electrically conductive one, such as well-known epoxy, B-stage epoxy or silicone, and the present invention does not limit the kind of the materials. If a well-known B-stage epoxy, which is half-dry at about 50°C,

is used as adhesive glue, the heat sink 31 will be firmly mounted to the die pad 14, the encapsulant 11 and a part of the plurality of leads 13 due to high pressures and high temperatures. The material of the heat sink 31 could be made of well-known copper, copper alloy, aluminum or aluminum alloy, and the present invention does not limit the kind of the materials.

As shown in FIG. 3(c), after the heat sink 31 mounted to the upper mold 18, a forming step is executed to bend the plurality of leads 13 towards the heat sink 31, and a singulating step is executed to cut off the four tie bars (not shown) of the leadframe.

The structure in FIG. 3(c) is to bend the plurality of leads towards the heat sink 31 in the forming step to form a so-called "cavity-up type" package. Another structure in FIG. 3(d) is to warp the plurality of leads towards the direction of the upper mold 18 in forming step to form a so-called "cavity-down type" package.

FIG. 4 shows an embodiment of a cavity-down package structure according to the present invention. In the structure of FIG. 4, the top of the heat sink 31 is further added a heat radiator 41 for dissipating the heat generated by the die 12 to the atmosphere by convection and radiation.

FIG. 5 shows an embodiment of a package structure according to the present invention. The difference between the embodiment in FIG. 4 and that in FIG. 5 is that the die pad 14 is a central-hole type, means that the die pad 14 could be split into two parts and left a central hole. The advantage of the design is to reduce the probability of delamination between the die 12 and the die pad 14. The heat sink 31 could be a T-shaped structure. After the encapsulation of the upper mold 18, the heat sink 31 is mounted to the second surface 122 of the die 12, the die pad 14 and the leads 13, and the manufacturing process is finished by the forming step and singulating step.

FIG. 6 shows another embodiment of a package structure according to the present invention. The difference from the above two embodiments

is that the package structure does not have a die pad, the die 12 is adhered to the leads 13 with die attach adhesive 15. The design is suitable to a leadframe mounted to the die of any sizes. As shown in FIGs. 3(b) and 3(c), after the encapsulation of the upper mold, the heat sink 31 is mounted to a part of the plurality of leads by the adhesive glue 32, and the manufacturing process is finished by the forming and singulating steps.

The heat sink 31 according to the invention is not inside the encapsulation. Therefore, even the CTEs of the heat sink 31 and the encapsulation are not the same, and the disadvantage of delamination will not occur due to the use of the adhesive glue as a buffering layer. Besides, cracks due to thermal stress would not be created. Therefore, the reliability of the package according to the present invention could be raised. Furthermore, the encapsulation is performed only in the upper mold. Therefore, there is no need to conduct a deflashing step as in the prior art because there is no flash on the heat sink. Although the bottom of the upper mold 18 would leave behind flash, the problem would be eliminated after the upper mold is mounted to the heat sink 31 with the adhesive glue 32, and the appearance and function of the semiconductor package according to the present invention will not be affected. In addition, as the die 12 and the plurality of leads 13 are mounted to the heat sink 31 with a thermally conductive adhesive glue 32, another heat dissipation path is formed and starts from the die 12, through the die pad 14, the heat sink 31, the plurality of leads 13, and to the printed circuit board (not shown) on which the package is mounted, in addition to the prior art path from the die 12, the die pad 14, the heat sink 31, and to the atmosphere.

The present invention does not limit the kind of the semiconductor packages, but is most suitable to the semiconductor packages of TQFP and TSOP.

The above-described embodiments of the present invention are intended to be illustrated only. Numerous alternative embodiments may be

devised by those skilled in the art without departing from the scope of the following claims.

100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000